


MAGNETIC RECORDING AND REPRODUCING DEVICE**Publication number:** JP8249758 (A)**Publication date:** 1996-09-27**Inventor(s):** ABE HIROCHIKA; NISHIJIMA HIDEO; TORII HIROYUKI;
KANIWA KOUJI; WATANABE KATSUYUKI**Applicant(s):** HITACHI LTD**Classification:****- international:** G11B5/027; G11B15/04; G11B15/07; G11B15/087; G11B20/00;
G11B5/027; G11B15/04; G11B15/05; G11B15/087; G11B20/00;
(IPC1-7); G11B15/07; G11B5/027; G11B15/04; G11B15/087;
G11B20/00**- European:****Application number:** JP19950055416 19950315**Priority number(s):** JP19950055416 19950315**Also published as:**

JP3336804 (B2)

Abstract of JP 8249758 (A)

PURPOSE: To omit the input setting operation by discriminating the kind of tapes, providing a mode for automatically setting the recording system and detecting the kind of cassette tapes from the existence of a detecting hole at the time of recording operation. **CONSTITUTION:** When the automatic discriminating mode is selected, the kind of cassettes is discriminated at the time point of receiving an instruction for recording by the operation of a recording button on a control panel 60. When it is discriminated to be D-cassette, it is judged that the digital recording is performed, and the digital signal input is selected by a switch 51 and also a digital signal processing circuit 54 is activated to start the recording operation. When it is not D-cassette, the setting of a manual mode changeover switch of the control panel 60 is ascertained; When the digital recording is selected and also in the case of S-cassette, the digital recording is started. The recording is not permitted in the case of V-cassette, and this effect is warned to the operator.



Data supplied from the esp@cenet database — Worldwide